

# BIPODS

## MAKE IT COUNT.

Purpose-built for every shooter. Whether recreational, competitive, and or professional we make a bipod with your name on it.

## JUMP TO A SERIES

- | **UTG PRO® TBNR® BIPODS** 116
- | **BIG BORE FULL STABILITY BIPOD** 118
- | **OVER BORE BIPOD** 120
- | **RECON FLEX® BIPODS** 122
- | **RECON 360® TL BIPODS** 124
- | **D GRIP®** 126
- | **QUICK DETACH BIPODS** 127

(THIRD PARTY TRADEMARKS MAY BE USED IN THIS CATALOG FOR USER CONVENIENCE TO INDICATE THE FIT OR COMPATIBILITY OF THE APPLICABLE PRODUCT.)



# THE BEST NEVER REST®



## TBNR® BIPODS | THE BEST NEVER REST



### OPTIONAL ACCESSORIES

#### QD ADJUSTABLE BIPOD FEET

- » Adjustable Rotary Turrets with Locking Collars Secure End User Height Adjustment
- » Compatible with UTG PRO® TBNR®, UTG® RECON FLEX® II, and Other QD Locking Detent Feet Bipods

1.65" - 1.93" Center Height / TL-BPLE01

#### M-LOK®

8.5" - 11.0" Center Height / TLUBP01M  
7.3" - 9.0" Center Height / TLUBP02M-A

#### PICATINNY


8.5" - 11.0" Center Height / TLUBP01  
7.3" - 9.1" Center Height / TLUBP02-A



## TBNR® BIPODS | THE BEST NEVER REST



Performance Tested and Evaluated



Height Adjustable Spiral Guided 7075-T6 Aluminum Leg Extensions with Automatic Leg Extension Retraction (US PAT. 10323897)



Tension Adjustable 360° Panning & 19° Tilt Forward, Rearward, Left, and Right



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup

	TLUBP01M	TLUBP02M-A	TLUBP01	TLUBP02-A
Mount Type	M-LOK®		Picatinny	
Center Height	8.5" - 11.0"	7.3" - 9.0"	8.5" - 11.0"	7.3" - 9.1"
Open Angle	50°	50°	50°	50°
Panning	360°	360°	360°	360°
Tilting	19°	19°	19°	19°
Foot Pad	Aluminum			
Weight	19.0 oz	17.2 oz	19.7 oz	18.3 oz
Extendable Legs	7 Position	4 Position	7 Position	4 Position
Leg Operation	Spring Loaded Retraction			



# BIG BORE FS

## BIG BORE FULL STABILITY BIPOD




### BIG BORE FULL STABILITY BIPOD

- » Matte Black Anodized Aluminum Construction with Reinforced Steel Components Designed from the Ground Up to Withstand Big Bore Calibers up to .50 BMG
- » Reinforced Picatinny Mounting Base Features a Longer Surface Area Equipped with a Squared Steel Crossbolt
- » Lockable and Height Adjustable Legs Provide a Center Height from 9"-14" and a Wide 70° Open Angle for Increased Stability
- » Posi-lock Push Buttons Feature a Large Surface Area for Easier Use while Wearing Gloves


9.4" - 14.0" Center Height / TL-BPFS01-A



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup



Tension Adjustable 35° Panning and 55° Left and Right Tilt



Rotatable Footpads Self Adjust to Uneven Surfaces and Bipod Leg Positioning

	TL-BPFS01-A
Mount Type	Picatinny
Center Height	9.4" - 14.0"
Open Angle	70°
Panning	35°
Tilting (Left/Right)	55°
Foot Pad	Steel
Weight	34.4 oz
Extendable Legs	9 Position
Leg Operation	Spring Loaded Retraction

# OVER BORE



## OVER BORE BIPOD




### OVER BORE BIPOD

- » Wide Open Angle Improves Stability
- » Matte Black Anodized Aircraft Aluminum Construction with Reinforced Steel Components
- » 3 Position Folding Legs Equipped with Rubberized Foot Pads
- » Lockable and Height Adjustable Legs Providing a Center Height from 7"-11"
- » 22° Panning and 44° Tension Adjustable Left and Right Tilt
- » Posi-lock Push Buttons Feature a Large Surface Area for Easier Use while Wearing Gloves

7.3" - 11.4" Center Height / TL-BPOB01-A



Quick Detachable Mounting Base (Designed to Mount Under or Over Rifle Bore)



0°, 45°, & 90° Folding Leg Positions with Steel-on-steel Lockup



Oversized Posi-lock Push Buttons for Easier Use while Wearing Gloves



Tension Adjustable 44° Left & Right Tilt

	TL-BPOB01-A
Mount Type	Picatinny
Center Height	7.3" - 11.4"
Open Angle	70°
Panning	22°
Tilting (Left/Right)	44°
Foot Pad	Rubberized
Weight	24.1 oz
Extendable Legs	7 Position
Leg Operation	Spring Loaded Retraction



# RECON FLEX®

## RECON FLEX® BIPODS



**RECON FLEX® II**  
 M-LOK® / 7.1" - 9.1" Center Height / TL-BPDM03  
 M-LOK® / 8.7" - 12.0" Center Height / TL-BPDM04



**RECON FLEX®**  
 M-LOK® / 5.7" - 8.0" Center Height / TL-BPDM01  
 M-LOK® / 8.0" - 11.8" Center Height / TL-BPDM02  
 KEYMOD / 5.7" - 8.0" Center Height / TL-BPDK01  
 KEYMOD / 8.0" - 11.8" Center Height / TL-BPDK02



WWW.LEAPERS.COM | SINCE 1992

### RECON FLEX® II BIPODS

- » 5 Position Bidirectional Legs Feature One-piece Locking Sliders with Circular Locking Lugs for Easier Manipulation and Added Durability
- » Interchangeable Foot Pads Compatible with Most Aftermarket Pads with QD Locking Detent
- » Automatic Leg Extension Deployment
- » Height Extendable Legs Lockable Via Thumb Wheel

### RECON FLEX® BIPODS

- » Ergonomic Spring Loaded Slide Locking Ring for Quick and Effortless Bipod Deployment
- » Legs with 5 Posi-lock Positions for Use on Different Firearms with Varying Height Clearance and Mounting Real Estate
- » Height Extendable Legs Lockable Via Thumb Wheel
- » US PAT. 10295292



Directly Attaches to Handguard at the 3 and 9 O'clock Positions



5 Position Bidirectional Folding Legs

	TL-BPDM03	TL-BPDM04	TL-BPDM01	TL-BPDM02	TL-BPDK01	TL-BPDK02
Mount Type	M-LOK®			Keymod		
Center Height	7.1" - 9.1"	8.7" - 12.0"	5.7" - 8.0"	8.0" - 11.8"	5.7" - 8.0"	8.0" - 11.8"
Open Angle	50°	50°	50°	50°	50°	50°
Foot Pad	Rubberized					
Weight	11.3 oz / 2pcs	12.3 oz / 2pcs	10.8 oz / 2pcs	13.7 oz / 2pcs	10.8 oz / 2pcs	13.5 oz / 2pcs
Extendable Legs	5 Position	7 Position	5 Position	7 Position	5 Position	7 Position
Leg Operation	Spring Loaded Extension			Manual		



# RECON 360®



## RECON 360® BIPODS

### M-LOK®

- 5.8" - 7.1" Center Height / TL-BPM02
- 6.6" - 9.1" Center Height / TL-BPM01
- 8.1" - 11.9" Center Height / TL-BPM03

US PAT. D758522

### PICATINNY

- 5.6" - 7.2" Center Height / TL-BP02-A
- 6.6" - 9.1" Center Height / TL-BP01-A
- 8.1" - 11.9" Center Height / TL-BP03-A

US PAT. D758521, US PAT. D758522



### RECON 360® TL BIPODS

- » Durable Aircraft Aluminum Construction Finished in a Matte Black Anodization
- » 3 Position Folding Legs and Lockable Leg Extensions Equipped with Nonslip Rubberized Foot Pads
- » Fine-tunable Tension Adjustment Lever Applies the User Desired Amount of Tension to the Bipod's 360° Panning & 15° Forward, Rearward, Left, and Right Tilt



0°, 45°, & 90° Folding Leg Positions



Fine-tunable Tension Adjustment Lever



15° Forward, Rearward, Left, and Right Tilt



360° Panning

	TL-BPM02	TL-BPM01	TL-BPM03	TL-BP02-A	TL-BP01-A	TL-BP03-A
Mount Type	M-LOK®			Picatinny		
Center Height	5.8" - 7.1"	6.6" - 9.1"	8.1" - 11.9"	5.6" - 7.2"	6.6" - 9.1"	8.1" - 11.9"
Open Angle	50°	50°	50°	50°	50°	50°
Panning	360°	360°	360°	360°	360°	360°
Tilting (Forward, Rearward, Left, & Right)	15°	15°	15°	15°	15°	15°
Foot Pad	Rubberized					
Weight	8.9 oz	11.3 oz	15.3 oz	10.9 oz	12.2 oz	14.5 oz
Extendable Legs	3 Position	5 Position	7 Position	3 Position	5 Position	7 Position
Leg Operation	Manual					



# D GRIP®



## D GRIP®

- » Contoured Foregrip with Nonslip and Heat-resistant Rubberized Inlays
- » Ambidextrous Quick Release Deploys Foldable Impact-resistant Bipod Legs Instantly
- » Quickly Transitions from Foregrip to Bipod
- » 5.6" Foregrip Length with an 8.4" Center Height and 65° Open Angle when Bipod is Deployed
- » US PAT. 8397421, US PAT. 9169958, EU REG: 002245522-0001, EU REG: 002245522-0002

/ **MNT-DG02Q**

	<b>MNT-DG02Q</b>
Mount Type	Picatinny
Center Height	8.4"
Open Angle	65°
Grip Height	5.6"
Bipod Height	8.6"
Foot Pad	Aluminum
Weight	12.7 oz
Leg Operation	Spring Loaded Deployment

# QUICK DETACH BIPODS



## RUBBER ARMORED QD BIPOD

- » Protected Rubber Armored Legs Stands up to the Harshes of Environments
- » 5 Position Extendable Legs Lockable via Thumb Wheel
- » 5 Position Bidirectional Folding Legs
- » US PAT. 8397421

**QD Lever Lock / 6.0" - 8.5" Center Height / TL-BP20Q-A**



## TACTICAL OP BIPODS

- » Heavy Duty Steel and Aluminum Construction with a Matte Black Finish
- » Spring-loaded Folding Legs
- » Fully Adjustable Legs with Locking Thumb Wheel & Automatic Retraction
- » US PAT. 8397421

**QD Lever Lock / 5.9" - 7.3" Center Height / TL-BP78Q**  
**QD Lever Lock / 8.0" - 12.4" Center Height / TL-BP88Q**  
**Locking Thumb Wheel / 6.1" - 7.9" Center Height / TL-BP78**  
**Locking Thumb Wheel / 8.3" - 12.7" Center Height / TL-BP88**



## SUPER DUTY QD BIPODS

- » Heavy Duty Steel and Aluminum Construction with a Matte Black Finish
- » Spring-loaded Folding Legs
- » Fully Adjustable Legs with Spring Loaded Retention Clamp and Locking Thumb Wheel
- » US PAT. 8397421

**QD Lever Lock / 6.0" - 8.5" Center Height / TL-BP98Q**  
**QD Lever Lock / 8.0" - 12.8" Center Height / TL-BP99Q**

## OPTIONAL ACCESSORIES

### SWIVEL STUD TO PICATINNY ADAPTOR

- » Steel and Aluminum Construction with Padded Adaptor Plate to Prevent Marring
- » Converts a Traditional Sling Swivel Stud to Accept Picatinny Mounted Bipods
- » Retains Swivel Stud Functionality for the Installation of a Sling when Installed
- » Quick to Install with No Permanent Modification Required

/ **TL-BPAD1**



### QD ADJUSTABLE BIPOD FEET

- » Adjustable Rotary Turrets with Locking Collars Secure End User Height Adjustment
- » Compatible with UTG PRO® TBNR®, UTG® RECON FLEX® II, and Other QD Locking Detent Feet Bipods

**1.65" - 1.93" Center Height / TL-BPLE01**



	<b>TL-BP20Q-A</b>	<b>TL-BP78Q</b>	<b>TL-BP88Q</b>	<b>TL-BP78</b>	<b>TL-BP88</b>	<b>TL-BP98Q</b>	<b>TL-BP99Q</b>
Mount Type	Picatinny						
Center Height	6.0" - 8.5"	5.9" - 7.3"	8.0" - 12.4"	6.1" - 7.9"	8.3" - 12.7"	6.0" - 8.5"	8.0" - 12.8"
Open Angle	50°	50°	50°	50°	50°	50°	50°
Panning	15°	15°	15°	15°	15°	15°	15°
Foot Pad	Rubberized						
Weight	14.0 oz	13.0 oz	12.8 oz	11.5 oz	13.3 oz	13.8 oz	17.4 oz
Extendable Legs	5 Position	3 Position	7 Position	3 Position	7 Position	5 Position	9 Position
Foldable Legs	5 Position	Yes					
Swivel Stud Kit	Included						
Leg Operation	Manual	Spring Loaded Retraction				Manual	